

1550 C Y L I N D R I C A L

V E R T I C A L V E N T C H E C K V A L V E

Wager is proud to announce our newest addition to our innovative line of vent check valves. The 1550 cylindrical valve is designed so that the body does not exceed the width of the flange. This allows the 1550 to fit nicely in confined spaces. Our design features a clear view of all the internal parts and allows for easy access during inspections.

In the open position, the 1550 allows for required airflows needed during loading and unloading of liquid or dry cargo. During heavy seas, our disc style float rises to a buna seat, and prevents contamination of tank cargo by seawater. (1.5" Uses ball float)

A 30 x 30 stainless steel flame screen provides protection from deck fires. The exterior design of the valve allows for added protection from debris.

The 1550 is available in galvanized steel, stainless steel, or aluminum. Sizes are 1.5" – 4". ABS Type Approved. Made in the USA.



MADE IN AMERICA

SPECIFICATIONS

AVAILABLE IN

STEEL (GALVANIZED)
ALUMINUM (ANODIZED)
316 SS

SIZE RANGE

1.5" - 4"

Valve reverse discharge/vacuum rating (80% of max):

1.5": 225.84 cfm @ 6" water column

2": 263.04 cfm @ 6" water column

2.5": 392.21 cfm @ 9.5" water column

3": 508.08 cfm @ 11" water column

4": 444.38 cfm @ 6" water column

PARTS LIST

QTY

- | | |
|---|---|
| 1 | 1. BODY |
| 1 | 2. CAP |
| 1 | 3. CAP GASKET |
| 1 | 4. SCREEN |
| 1 | 5. SEAT |
| 1 | 6. FLOAT |
| 1 | 7. GUIDE ROD* (1.5" MODEL USES BALL FLOAT) |
| 1 | 8. COVER |
| 9 | 9. BOLTS |